

**PROPRIETARY NOTE**

THIS SPECIFICATION IS THE PROPERTY OF BOEFZ AND SHALL NOT BE  
REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOEFZ AND  
MUST BE RETURNED TO BOEFZ UPON ITS REQUEST

SPEC. NUMBER  
S8-65-8D-229

PRODUCT GROUP  
TFT-LCD

Rev. A

ISSUE DATE  
2023.03.21

PAGE  
1 OF 34

**DV170E0M-N30**

**Product Specification.A**

Fuzhou BOE Optoelectronics Technology Co.,Ltd

**BOE****PRODUCT GROUP****REV****ISSUE DATE**

TFT- LCD PRODUCT

A

2023.03.21

SPEC. NUMBER  
S8-65-8D-229SPEC. TITLE  
DV170E0M-N30 Product SpecificationPAGE  
2 OF 34**REVISION HISTORY**

REV.	ECN No.	DESCRIPTION OF CHANGES	DATE	PREPARED
O	-	Initial Release	2021.12.01	jiangdongdong
A		Update display direction、7*20hr usage	2023.03.21	Jingrui Ren



## PRODUCT GROUP

TFT- LCD PRODUCT

REV

ISSUE DATE

A

2023.03.21

SPEC. NUMBER  
S8-65-8D-229

SPEC. TITLE  
DV170E0M-N30 Product Specification

PAGE  
3 OF 34


## Contents

No	ITEM	Page
	REVISIONS HISTORY	2
	CONTENTS	3
1	GENERAL DESCRIPTION	4
	1.1 Introduction	
	1.2 Features	
	1.3 Applications	
	1.4 General Specification	
2	ABSOLUTE MAXIMUM RATINGS	6
3	ELECTRICAL SPECIFICATIONS	7
	3.1 TFT LCD Open Cell	
	3.2 Backlight Unit	
4	INTERFACE CONNECTION	9
	4.1 Open Cell Input Signal & Power	
	4.2 LVDS Interface	
	4.3 LVDS Rx Interface Timing Parameter	
	4.4 LVDS Rx Interface Eye Diagram	
	4.5 LVDS Receiver Differential Input	
5	SIGNAL TIMING SPECIFICATIONS	14
	5.1 Timing Parameters (DE only mode)	
	5.2 Signal Timing Waveform	
	5.3 Input Signals, Basic Display Colors and Gray Scale of Colors	
	5.4 Power Sequence	
6	OPTICAL SPECIFICATIONS	19
7	MECHANICAL CHARACTERISTICS	21
8	RELIABILITY TEST	22
9	PRODCUT SERIAL NUMBER	23
10	PACKING INFORMATION	24
11	PRECAUTIONS	26
12	APPENDIX	31

## 1.0 GENERAL DESCRIPTION

### 1.1 Introduction

DV170E0M-N30 is a color active matrix TFT LCD MDL using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This MDL has a 17 inch diagonally measured active area with SXGA resolutions (1280 horizontal by 1024 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 16.7M colors. The TFT-LCD MDL panel is adapted for a low reflection and higher color type.



### 1.2 Features

- LVDS interface with 2 pixel / clock
- High-speed response
- Low color shift image quality
- 6-bit+FRC color depth, display 16.7M colors
- Wide viewing angle
- DE (Data Enable) only mode
- IHADS technology is applied for high display quality
- RoHS compliant
- 7\*20hrs usage support with dynamic video
- Landscape and Portrait usage support

<b>BOE</b>	<b>PRODUCT GROUP</b>	<b>REV</b>	<b>ISSUE DATE</b>
	TFT- LCD PRODUCT	A	2023.03.21
SPEC. NUMBER S8-65-8D-229	SPEC. TITLE DV170E0M-N30 Product Specification		PAGE 5 OF 34

### 1.3 Application

- Commercial Digital Display
- Display Terminals for Control System
- Landscape and Portrait Display

### 1.4 General Specification

< Table 1. General Specifications >

Parameter	Specification	Unit	Remarks
Active area	337.92(H) × 270.336 (V)	mm	
Number of pixels	1280(H) × 1024(V)	pixels	
Pixel pitch	0.264(H) × 0.264(V)	mm	
Pixel arrangement	Pixels RGB Vertical stripe		
Display colors	16.7M	colors	6bits+FRC
Display mode	Normally Black		
Dimensional outline	358.5(H) × 296.5V) × 7.7 (Body)	mm	Detail refer to drawing
Weight	1350(typ.)	g	
Power Consumption	3W ( OC ) + 9.984W BLU	Watt	Typ. (Estimated)
Bezel width (L/R/U/D)	8.39/8.39/11.18/11.18	mm	
Surface Treatment	Haze 25%, 3H		
Back-light	Lower side E-LED Light bar Type		
Display Direction	landscape & Portrait		

## 2.0 ABSOLUTE MAXIMUM RATINGS


The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. Open Cell Electrical Specifications >

[VSS=GND=0V]

Parameter	Symbol	Min.	Max.	Unit	Remark
Power Supply Voltage	VDD	-0.3	5.5	V	T <sub>a</sub> = 25 °C
Operating Temperature	T <sub>OP</sub>	-20	+70	°C	
Storage Temperature	T <sub>SUR</sub>	-30	+70	°C	Note 1
	T <sub>ST</sub>	-30	+70	°C	
Operating Ambient Humidity	H <sub>OP</sub>	10	80	%RH	
Storage Humidity	H <sub>ST</sub>	10	80	%RH	

Note 1 : Temperature and relative humidity range are shown in the figure below.  
Wet bulb temperature should be 39 °C max. and no condensation of water.



## 3.0 ELECTRICAL SPECIFICATIONS

## 3.1 TFT LCD Open Cell

&lt; Table 3. Open Cell Electrical Specifications &gt;

[Ta = 25±2 °C]

Parameter	Symbol	Values			Unit	Remark
		Min	Typ	Max		
Power Supply Input Voltage	VDD	4.5	5	5.5	V	Note 1
Power Supply Current	IDD	-	600	1000	mA	
Power Supply Ripple Voltage	VRP	-	-	300	mV	
Rush Current	IRUSH	-	2	3	A	Note 2
LVDS Interface	Differential Input High Threshold Voltage	VLVTH	-	-	+100	mV
	Differential Input Low Threshold Voltage	VLVTL	-100	-	-	mV
	Common Input Voltage	VLVC	0.7	-	1.6	V
CMOS Interface	Input High Threshold Voltage	VIH	0.7VDD	-	VDD	V
	Input Low Threshold Voltage	VIL	0	-	0.3VDD	V
Power Consumption	PD	-	3	5.5	W	
	PBL	8.424	9.36	9.984	W	Note 3


Note 1 : The supply voltage is measured and specified at the interface connector of LCM.

The current draw and power consumption specified is for VDD=5.0V,


Frame rate  $f_v$ =60Hz and Clock frequency = 54MHz.

Test Pattern of power supply current

a) Typ : Mosaic 7X5 (L0/L255)



b) Max : Vline Subline (L255 )



Note 2 : The duration of rush current is about 2ms and rising time of Power Input is 1ms(min)

Note 3 : Calculated value for reference (Input pins\*VPIN × IPIN) excluding inverter loss.



## PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

A

2023.03.21

SPEC. NUMBER  
S8-65-8D-229

SPEC. TITLE  
DV170E0M-N30 Product Specification

PAGE  
8 OF 34

## 3.0 ELECTRICAL SPECIFICATIONS

### 3.2 Backlight Unit

< Table 3. Backlight Unit Electrical Specifications >

[ $T_a = 25 \pm 2 {}^\circ C$ ]

Parameter		Min.	Typ.	Max.	Unit	Remarks
LED Light Bar Input Voltage Per Input Pin	VPIN	32.4	36	38.4	V	Duty 100%
LED Light Bar Input Current Per Input Pin	IPIN		65		mA	Note1,2,
LED Power Consumption	PBL	8.424	9.36	9.984	W	Note 3
LED Life-Time	-	30,000	-		Hrs	Note 4

LED bar consists of 48LED packages,4 strings(parallel)\*12packages(serial)

Note1: There are one light bar ,and the specified current is input LED chip 100% duty current

Note2: The sense current of each input pin is 65mA

Note3:  $PBL = 4 \text{ Input pins} \times VPIN \times IPIN$

Note4: The lifetime is determined as the time at which luminance of LED become 50% of the initial brightness or not normal lighting at  $IPIN=65mA$  on condition of continuous operating at  $25 \pm 2 {}^\circ C$



## PRODUCT GROUP

TFT- LCD PRODUCT

REV

ISSUE DATE

A

2023.03.21

SPEC. NUMBER  
S8-65-8D-229

SPEC. TITLE  
DV170E0M-N30 Product Specification

PAGE  
9 OF 34

## 4.0 INTERFACE CONNECTION

### 4.1 Open Cell Input Signal & Power

- LVDS Connector : MSBKT2407P30-HC(STM) /IS100-L30O-C23 (UJU) or equivalent
- < Table 4. Open Cell Input Connector Pin Configuration >

Pin No	Symbol	Description	Pin No	Symbol	Description
1	RXO0-	Negative LVDS differential data input(Odd data)	16	RXE1+	Positive LVDS differential data input(Even data)
2	RXO0+	Positive LVDS differential data input(Odd data)	17	GND	Ground
3	RXO1-	Negative LVDS differential data input(Odd data)	18	RXE2-	Negative LVDS differential data input(Even data)
4	RXO1+	Positive LVDS differential data input(Odd data)	19	RXE2+	Positive LVDS differential data input(Even data)
5	RXO2-	Negative LVDS differential data input(Odd data)	20	RXEC-	Negative LVDS differential data input(Even clock)
6	RXO2+	Positive LVDS differential data input(Odd data)	21	RXEC+	Positive LVDS differential data input(Even clock)
7	GND	Ground	22	RXE3-	Negative LVDS differential data input(Even data)
8	RXOC-	Negative LVDS differential data input(Odd clock)	23	RXE3+	Positive LVDS differential data input(Even data)
9	RXOC+	Positive LVDS differential data input(Odd clock)	24	GND	Ground
10	RXO3-	Negative LVDS differential data input(Odd data)	25	NC	No connection(for BOE internal use)
11	RXO3+	Positive LVDS differential data input(Odd data)	26	NC	No connection(for BOE internal use)
12	RXE0-	Negative LVDS differential data input(Even data)	27	NC	No connection(for BOE internal use)
13	RXE0+	Positive LVDS differential data input(Even data)	28	VDD	
14	GND	Ground	29	VDD	Power Supply: +5V
15	RXE1-	Negative LVDS differential data input(Even data)	30	VDD	



## PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

A

2023.03.21

SPEC. NUMBER  
S8-65-8D-229SPEC. TITLE  
DV170E0M-N30 Product SpecificationPAGE  
10 OF 34

## 4.2 LED Light Bar


-LED connector : 3707K-S06N-21L(ENTRY) or Compatible

&lt; Table 5. LED Light Bar&gt;

Pin No	Symbol	Description
1	IRLED1	LED current sense for string1
2	IRLED2	LED current sense for string2
3	VLED	LED power supply
4	VLED	LED power supply
5	IRLED3	LED current sense for string3
6	IRLED4	LED current sense for string4

Notes : 1. NC(Not Connected) : This pins are only used for BOE internal operations.  
2. Input Level of LVDS signal is based on the EIA-644 Standard.

### BIST Pattern





## PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

A

2023.03.21

SPEC. NUMBER  
S8-65-8D-229

SPEC. TITLE  
DV170E0M-N30 Product Specification

PAGE  
12 OF 34

### 4.2 LVDS Interface

- LVDS Receiver : Timing Controller (LVDS Rx merged) / LVDS Data : Pixel Data
- < Table 6. Open Cell Input Connector Pin Configuration >


Input Signal	Transmitter		Interface		HT236F01-100 (CN 11)	Remark
	Pin No.	Pin No.	System (Tx)	TFT-LCD (Rx)		
LVDS	OR0	51	48	OUT0- OUT0+	RX00- RX00+	1
	OR1	52				2
	OR2	54				
	OR3	55				
	OR4	56				
	OR5	3				
	OG0	4				
	OG1	6	46	OUT1- OUT1+	RX01- RX01+	3
	OG2	7				4
	OG3	11				
	OG4	12				
	OG5	14				
	OB0	15				
	OB1	19				
	OB2	20	42	OUT2- OUT2+	RX02- RX02+	5
	OB3	22				6
	OB4	23				
	OB5	24				
	Hsync	27				
	Vsync	28				
	DE	30				
	MCLK	31	40	CLK OUT- CLK OUT+	RX0 CLK- RX0 CLK+	8 9
	OR6	50	38	OUT3- OUT3+	RX03- RX03+	
	OR7	2				
	OG6	8				
	OG7	10				10
	OB6	16				11
	OB7	18				
	RSVD	25				

## 4.3 LVDS Rx Interface Timing Parameter

The specification of the LVDS Rx interface timing parameter is shown in Table 6.

<Table 7. LVDS Rx Interface Timing Specification>

Item	Symbol	Min	Typ	Max	Unit	Remark
CLKIN Period	tRCIP	17.5	18.5	19.6	nsec	
Input Data 0	tRIP1	$0.5 \times tRCIP/7 - 0.4$	$0.5 \times tRCIP/7$	$0.5 \times tRCIP/7 + 0.4$	nsec	
Input Data 1	tRIP0	$1.5 \times tRCIP/7 - 0.4$	$1.5 \times tRCIP/7$	$1.5 \times tRCIP/7 + 0.4$	nsec	
Input Data 2	tRIP6	$2.5 \times tRCIP/7 - 0.4$	$2.5 \times tRCIP/7$	$2.5 \times tRCIP/7 + 0.4$	nsec	
Input Data 3	tRIP5	$3.5 \times tRCIP/7 - 0.4$	$3.5 \times tRCIP/7$	$3.5 \times tRCIP/7 + 0.4$	nsec	
Input Data 4	tRIP4	$4.5 \times tRCIP/7 - 0.4$	$4.5 \times tRCIP/7$	$4.5 \times tRCIP/7 + 0.4$	nsec	
Input Data 5	tRIP3	$5.5 \times tRCIP/7 - 0.4$	$5.5 \times tRCIP/7$	$5.5 \times tRCIP/7 + 0.4$	nsec	
Input Data 6	tRIP2	$6.5 \times tRCIP/7 - 0.4$	$6.5 \times tRCIP/7$	$6.5 \times tRCIP/7 + 0.4$	nsec	



\*  $V_{diff} = (RXz+) - (RXz-), \dots, (RXCLK+) - (RXCLK-)$

<b>BOE</b>	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	A	2023.03.21
SPEC. NUMBER S8-65-8D-229	SPEC. TITLE DV170E0M-N30 Product Specification		PAGE 14 OF 34

## 5.0 SIGNAL TIMING SPECIFICATION

### 5.1 Timing Parameters (DE only mode)

< Table 8. Timing Table >

Item		Symbols	Min	Typ	Max	Unit
Clock	Frequency	1/Tc	51	54	57	MHz
	High Time	Tch	-	4/7Tc	-	
	Low Time	Tcl	-	3/7Tc	-	
Frame Period		Tv	57	60	75	Hz
Horizontal Active Display Term	Valid	t <sub>HV</sub>	-	640	-	t <sub>CLK</sub>
	Total	t <sub>HP</sub>	730	844	940	t <sub>CLK</sub>
Vertical Active Display Term	Valid	t <sub>VV</sub>	-	1024	-	t <sub>HP</sub>
	Total	t <sub>VP</sub>	1037	1066	1096	t <sub>HP</sub>


Notes: This product is DE only mode. The input of Hsync & Vsync signal does not have an effect on normal operation.

< Table 9. LVDS Input SSCG >

Symbol	Parameter	Condition	Min	Typ	Max	Unit
F	LVDS Input frequency	-	30	-	110	MHz
T <sub>LVSK</sub>	LVDS channel to channel skew	F=75MHz V <sub>IC</sub> =1.2V V <sub>ID</sub> =±200mV	-400	-	+400	ps
F <sub>LVMOD</sub>	Modulating frequency of input clock during SSC	F=75MHz V <sub>IC</sub> =1.2V V <sub>ID</sub> =±200mV	10	-	300	KHz
F <sub>LVDEV</sub>	Maximum deviation of input clock frequency during SSC	F=75MHz V <sub>IC</sub> =1.2V V <sub>ID</sub> =±200mV	-3	-	+3	%
T <sub>CY-CY</sub>	Cycle to Cycle jitter		-	-	200	ps


## 5.2 Signal Timing Waveform

### 5.2.1 Sync Timing Waveform





- 1) Need over 3 H-sync during V-Sync Low
- 2) Fix H-Sync width from V-Sync falling edge to first rising edge

### 5.2.2 Vertical Timing Waveform



## 5.2.3 Horizontal Timing Waveform




## 5.3 Input Signals, Basic Display Colors and Gray Scale of Colors

&lt; Table 10. Input Signal and Display Color Table &gt;

Color & Gray Scale		Input Data Signal																									
		Red Data								Green Data								Blue Data									
		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0		
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1		
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0		
	Cyan	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
	Magenta	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1		
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0		
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		
Gray Scale of Red	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
	Darker	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
	△	↑								↑								↑									
	▽	↓								↓								↓									
	Brighter	1	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
	▽	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
Gray Scale of Green	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	
	△	↑								↑								↑									
	▽	↓								↓								↓									
	Brighter	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	
Gray Scale of Blue	▽	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	
	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	1	0
	△	↑								↑								↑									
	▽	↓								↓								↓									
Gray Scale of White	Brighter	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1	
	▽	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1								

## 5.4 Power Sequence

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below



< Table 11. Sequence Table >

Parameter	Values			Units
	Min	Typ	Max	
T1	0.5	-	10	ms
T2	0	-	50	ms
T3	500	-	-	ms
T4	500	-	-	ms
T5	0	-	30	ms
T6	1	-	-	s
T7	0	-	10	ms

Notes:

1. Back Light must be turn on after power for logic and interface signal are valid.
2. Even though T1 is out of SPEC, it is still ok if the inrush current of VDD is below the limit.
3. When VDD<0.9VDD(Typ.), Power off.
4. T7 decreases smoothly, if there were rebounding voltage, it must smaller than 0.5 volts.

<b>BOE</b>	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	A	2023.03.21
SPEC. NUMBER S8-65-8D-229	SPEC. TITLE DV170E0M-N30 Product Specification		PAGE 19 OF 34

## 6.0 OPTICAL SPECIFICATIONS

The test of optical specifications shall be measured in a dark room (ambient luminance  $\leq 1$  lux and temperature  $= 25 \pm 2^\circ\text{C}$ ) with the equipment of Luminance meter system (Goniometer system and PR788) and test unit shall be located at an approximate distance 180cm from the LCD surface at a viewing angle of  $\theta$  and  $\Phi$  equal to  $0^\circ$ . We refer to  $\theta_{\phi=0}$  ( $= \theta_3$ ) as the 3 o'clock direction (the "right"),  $\theta_{\phi=90}$  ( $= \theta_{12}$ ) as the 12 o'clock direction ("upward"),  $\theta_{\phi=180}$  ( $= \theta_9$ ) as the 9 o'clock direction ("left") and  $\theta_{\phi=270}$  ( $= \theta_6$ ) as the 6 o'clock direction ("bottom"). While scanning  $\theta$  and/or  $\phi$ , the center of the measuring spot on the Display surface shall stay fixed. The measurement shall be executed after 30 minutes warm-up period. VDD shall be 5.0V at  $25^\circ\text{C}$ .

< Table 12. Optical Table >

[VDD = 5.0V, Frame rate = 60Hz, Ta =  $25 \pm 2^\circ\text{C}$ ]

Parameter		Symbol	Condition	Min	Typ	Max	Unit	Remark	
Viewing Angle	Horizontal	$\theta_3$	CR > 10	85	89		Deg.	Note 1	
		$\theta_9$		85	89		Deg.		
	Vertical	$\theta_{12}$		85	89		Deg.		
		$\theta_6$		85	89		Deg.		
Brightness		$L_v$	$\Theta = 0^\circ$ ILED=55mA	450	500		nit		
Uniformity	9 Points	$\Delta Y9$		75%	80%	-		Note 2	
Contrast ratio		CR	$\Theta = 0^\circ$	700:1	1000:1	-		Note 3	
Reproduction of color	White	$W_x$	$\Theta = 0^\circ$ (Center) Normal Viewing Angle	0.313	TYP. - 0.03	TYP. + 0.03		Note 4	
		$W_y$		0.329					
	Red	$R_x$		0.650					
		$R_y$		0.339					
	Green	$G_x$		0.324					
		$G_y$		0.619					
	Blue	$B_x$		0.153					
		$B_y$		0.056					
Color Gamut				68	72	-	%		
Response Time		Tr + Tf		-	20		ms	Note 5	
Gamma Scale				2.0	2.2	2.4			

<b>BOE</b>	<b>PRODUCT GROUP</b>	<b>REV</b>	<b>ISSUE DATE</b>
	TFT- LCD PRODUCT	A	2023.03.21
<b>SPEC. NUMBER</b> S8-65-8D-229	<b>SPEC. TITLE</b> DV170E0M-N30 Product Specification		<b>PAGE</b> 20 OF 34

Note :

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface.
2. The White luminance uniformity on LCD surface is then expressed as :  $\Delta Y = \text{Minimum Luminance of 9 points} / \text{Maximum Luminance of 9 points}$ . (see Figure 1 shown in Appendix).
3. Contrast measurements shall be made at viewing angle of  $\theta = 0^\circ$  and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state. (See Figure 2 shown in Appendix) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

4. The color chromaticity coordinates specified in Table 12 shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel. The BLU is used by BOE.
5. The electro-optical response time measurements shall be made as Figure 3 when the input signal are changed from "black" to "white" and from "white" to "black" ), respectively .The response time is defined as the time interval between the 10% and 90% of amplitudes .



## PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

A

2023.03.21

SPEC. NUMBER  
S8-65-8D-229

SPEC. TITLE  
DV170E0M-N30 Product Specification

PAGE  
21 OF 34

## 7.0 MECHANICAL CHARACTERISTICS

### 7.1 Dimensional Requirements

Figure 3(located in Appendix) shows mechanical outlines for the model DV170YGM-N10 . Other parameters are shown in Table 13.

< Table 13. Dimensional Parameters >

Parameter	Specification	Unit
<u>Dimensional outline</u> <u>e</u>	358.5(H) × 296.5 (V) × 7.7 (Body)	<u>mm</u>
Weight	1350(Typ.)	gram
Active area	337.92(H) × 270.336(V)	mm
Pixel pitch	0.264(H) × 0.264(V)	mm
Number of pixels	1280(H) × 1024(V) (1 pixel = R + G + B dots)	pixels

### 7.2 Mounting

See FIGURE 5. (shown in Appendix)

### 7.3 Anti-Glare and Polarizer Hardness.

The surface of the LCD has an anti-glare coating to minimize reflection and a coating to reduce scratching.

<b>BOE</b>	<b>PRODUCT GROUP</b>	<b>REV</b>	<b>ISSUE DATE</b>
	TFT- LCD PRODUCT	A	2023.03.21
SPEC. NUMBER S8-65-8D-229	SPEC. TITLE DV170E0M-N30 Product Specification		PAGE 22 OF 34

## 8.0 RELIABILITY TEST

The Reliability test items and its conditions are shown in below.

< Table 14. Reliability Test Parameters >

<b>No</b>	<b>Test Items</b>	<b>Conditions</b>
1	High temperature storage test	Ta = 70 °C, 240 hrs
2	Low temperature storage test	Ta = -30 °C, 240 hrs
3	High temperature & high humidity operation test	Ta = 70 °C, 80%RH, 240hrs
4	High temperature operation test	Ta = 70 °C, 240hrs
5	Low temperature operation test	Ta = -20 °C, 240hrs
6	Thermal shock	Ta = -20 °C ↔ 60 °C (per 0.5 hr), 100 cycle

This test condition is based on BOE module.

**BOE****PRODUCT GROUP**


REV

ISSUE DATE

TFT- LCD PRODUCT

A

2023.03.21

SPEC. NUMBER  
S8-65-8D-229SPEC. TITLE  
DV170E0M-N30 Product SpecificationPAGE  
23 OF 34**9.0 PRODCUT SERIAL NUMBER**

MDL ID Naming Rule:

Digit Code	1	2	3	4	5	6	7	8	9	10	11				
Description	Model Code GBN		Grade	Line	Year		Month	Model Extension Code							
Digit Code	12	13	14	15	16	17	18								
Description	Serial No						扫码不显示，BOE厂内用								

## 10.0 PACKING INFORMATION



BOE provides the standard shipping container for customers, unless customer specifies their packing information. The standard packing method and Barcode information are shown in below.

### 10.1 Packing Order

Put 2 EPE bottom into the inner box.



Put each module into a PE bag.  
Insert 14Pcs MDL into each box



-Put the boxes on the Pallet  
14boxes/Pallet:4boxes per layer, total 4  
layers

-Place paper corners and wrap film around  
the boxes

-Pack with 2 packing belts

Put 2 EPE cover in and seal the box.

<b>BOE</b>	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	A	2023.03.21
SPEC. NUMBER S8-65-8D-229	SPEC. TITLE DV170E0M-N30 Product Specification		PAGE 25 OF 34

## 10.2 Packing Note

- Box Dimension : 512mm(L)×442mm(W)×357mm(H)
- Package Quantity in one Box : 14pcs

## 10.3 Box Label - Module

- Label Size : 100 mm (L) × 50 mm (W)


- Contents

Model : DV170E0M-N30

Q'ty : Module 14 Q'ty in one box

Serial No. : Box Serial No.

Date : Packing Date



<b>BOE</b>	<b>PRODUCT GROUP</b>	<b>REV</b>	<b>ISSUE DATE</b>
	TFT- LCD PRODUCT	A	2023.03.21
SPEC. NUMBER S8-65-8D-229	SPEC. TITLE DV170E0M-N30 Product Specification		PAGE 26 OF 34

## 11.0 PRECAUTIONS

Please pay attention to the followings when you use this TFT LCD Module.

### 11.1 Mounting Precautions

- Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- You must mount a module using specified mounting holes (Details refer to the drawings)
- You should consider the mounting structure so that uneven force (ex. Twisted stress, Concentrated stress) is not applied to the module. And the case on which a module is mounted should have sufficient strength so that external force is not transmitted directly to the module.
- Do not apply mechanical stress or static pressure on module; Abnormal display cause by pressing some parts of module during assembly process , do not belong to product failure, the press should be agreed by two sides.
- Determine the optimum mounting angle, refer to the viewing angle range in the specification for each model.
- Do not apply mechanical stress or static pressure on module , and avoid impact, vibration and falling.
- Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the polarizer at high temperature and the latter causes circuit break by electro-chemical reaction.
- Protection film for polarizer on the module should be slowly peeled off before display.
- Be careful to prevent water & chemicals contact the module surface.
- You should adopt radiation structure to satisfy the temperature specification.
- Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment. Do not touch the surface of polarizer for bare hand or greasy cloth.(Some cosmetics are detrimental to the polarizer.)
- When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with petroleum benzine. Normal-hexane & alcohol is recommended for cleaning the adhesives used to attach front / rear polarizers. Do not use acetone, toluene , because they cause chemical damage to the polarizer.
- Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading..

<b>BOE</b>	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	A	2023.03.21
SPEC. NUMBER S8-65-8D-229	SPEC. TITLE DV170E0M-N30 Product Specification		PAGE 27 OF 34
<ul style="list-style-type: none"> <li>• This module has its circuitry PCB's on the rear side and Driver IC, should be handled carefully in order not to be stressed.</li> <li>• Avoid impose stress on PCB and Driver IC during assembly process ,Do not drawing, bending, COF package &amp; wire</li> <li>• Do not disassemble the module.</li> </ul>			
<h3>11.2 Operating Precautions</h3> <ul style="list-style-type: none"> <li>• Do not connector or disconnect the cable to/from the Module at the “Power On” Condition.</li> <li>• When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the module would be damaged.</li> <li>• Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.</li> <li>• Do not allow to adjust the adjustable resistance or switch</li> <li>• The electrochemical reaction caused by DC voltage will lead to LCD module degradation, so DC drive should be avoided.</li> <li>• The LCD modules use C-MOS drivers, so customers are recommended that any unused input terminal would be connected to Vdd or Vss, do not input any signals before power is turn on, and ground you body, work/assembly area, assembly equipment to protect against static electricity.</li> <li>• Do not exceed the absolute maximum rating value. (supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on) Otherwise the Module may be damaged.</li> <li>• Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimized the interference.</li> <li>• Design the length of cable to connect between the connector for back-light and the converter as shorter as possible and the shorter cable shall be connected directly , The long cable between back-light and Converter may cause the Luminance of LED to lower and need a higher startup voltage</li> <li>• The cables should be as short as possible between System Board and PCB interface.</li> <li>• Connectors are precision devices to transmit electrical signals, and operators should plug in parallel</li> <li>• Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.</li> </ul>			

<b>BOE</b>	<b>PRODUCT GROUP</b>	<b>REV</b>	<b>ISSUE DATE</b>
	TFT- LCD PRODUCT	A	2023.03.21
SPEC. NUMBER S8-65-8D-229	SPEC. TITLE DV170E0M-N30 Product Specification		PAGE 28 OF 34

### 11.3 Electrostatic Discharge Precautions

- Avoid the use work clothing made of synthetic fibers. We recommend cotton clothing or other conductivity-treated fibers.
- Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc.
- Do not close to static electricity to avoid product damage.
- Do not touch interface pin directly.

### 11.4 Precautions for Strong Light Exposure

- Do not leave the module operation or storage in Strong light . Strong light exposure causes degradation of polarizer and color filter.

### 11.5 Precautions for Storage

#### A. Atmosphere Requirement

ITEM	UNIT	MIN	MAX
Storage Temperature	(°C)	5	40
Storage Humidity	(%orII)	40	75
Storage Life	6 months		
Storage Condition	<ul style="list-style-type: none"> <li>• The storage room should be equipped with a dark and good ventilation facility.</li> <li>• Prevent products from being exposed to the direct sunlight, moisture and water.</li> <li>• The product need to keep away from organic solvent and corrosive gas.</li> <li>• Be careful for condensation at sudden temperature change.</li> <li>• Storage condition is guaranteed under packing conditions.</li> </ul>		

#### B. Package Requirement

- The product should be placed in a sealed polythene bag.
- Product Should be placed on the pallet, Which is away from the floor, Be cautions not to pile the product up.
- The polarizer surface should not come in contact with any other object. It is recommended that they be stored in the container in which they were shipped.
- As the original protective film, do not use the adhesive protective film to avoid change of Pol color and characteristic.

<b>BOE</b>	<b>PRODUCT GROUP</b>	<b>REV</b>	<b>ISSUE DATE</b>
	TFT- LCD PRODUCT	A	2023.03.21
SPEC. NUMBER S8-65-8D-229	SPEC. TITLE DV170E0M-N30 Product Specification		PAGE 29 OF 34

## 11.6 Precautions for protection film

- Remove the protective film slowly, keeping the removing direction approximate 30-degree not vertical from panel surface, If possible, under ESD control device like ion blower, and the humidity of working room should be kept over 50%RH to reduce the risk of static charge.
- People who peeled off the protection film should wear anti-static strap and grounded well.

## 11.7 Appropriate Condition for Commercial Display

-Generally large-sized LCD modules are designed for consumer applications . Accordingly, long-term display like in Commercial Display application, can cause uneven display including image sticking. To optimize module's lifetime and function, several operating usages are required.

### 1. Normal operating condition

- Temperature:  $20 \pm 15^{\circ}\text{C}$
- Operating Ambient Humidity :  $55 \pm 20\%$
- Display pattern: dynamic pattern (Real display)
- Well-ventilated place is recommended to set up Commercial Display system

### 2. Special operating condition

#### a. Ambient condition

- Well-ventilated place is recommended to set up Commercial Display system.

#### b. Power and screen save

- Periodical power-off or screen save is needed after long-term display.

c. As the low temperature, the response time is greatly delayed. As the high temperatures (higher than the operating temperature) the LCD module may turn black screen. The above phenomenon cannot explain the failure of the display. When the temperature returns to the normal operating temperature, the LCD module will return to normal display.

d. When expose to drastic fluctuation of temperature (hot to cold or cold to hot ) ,the LCD module may be affected; Specifically, drastic temperature fluctuation from cold to hot ,produces

dew on the LCD module 's surface which may affect the operation of the polarizer and LCD module

e. Do not exceed the absolute maximum rating value. (supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on) Otherwise the Module may be damaged.

<b>BOE</b>	<b>PRODUCT GROUP</b>	<b>REV</b>	<b>ISSUE DATE</b>
	TFT- LCD PRODUCT	A	2023.03.21
<b>SPEC. NUMBER</b> S8-65-8D-229	<b>SPEC. TITLE</b> DV170E0M-N30 Product Specification		<b>PAGE</b> 30 OF 34

f. Product reliability and functions are only guaranteed when the product is used under right operation usages. If product will be used in extreme conditions such as high temperature, high humidity, high altitude, special display images, running time, long time operation, outdoor operation, etc. It is strongly recommended to contact BOE for filed application engineering advice. Otherwise, its reliability and function may not be guaranteed. Extreme conditions are commonly found at airports, transit stations, banks, stock market and controlling systems.

3. Operating usages to protect against image sticking due to long-term static display.

- a. Suitable operating time: under 20 hours a day.
- b. Static information display recommended to use with moving image.
  - Cycling display between 5 minutes' information(static) display and 10 seconds' moving image.
- c. Background and character (image) color change
  - Use different colors for background and character, respectively.
  - Change colors themselves periodically.
- d. Avoid combination of background and character with large different luminance.
  - 1) Abnormal condition just means conditions except normal condition.
  - 2) Black image or moving image is strongly recommended as a screen save

4. Lifetime in this spec. is guaranteed only when Commercial Display is used according to operating usages.

## 11.8 Other Precautions

### A. LC Leak

- If the liquid crystal material leaks from the panel, it is recommended to wash the LC with acetone or ethanol and then burn it.
- If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, skin or clothes, it has to be washed away thoroughly with soap.
- If LC in mouth, mouth need to be washed, drink plenty of water to induce vomiting and follow medical advice.
- If LC touch eyes, eyes need to be washed with running water at least 15 minutes.

### B. Rework

- When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

**BOE****PRODUCT GROUP****REV****ISSUE DATE**

TFT- LCD PRODUCT


A

2023.03.21

SPEC. NUMBER  
S8-65-8D-229SPEC. TITLE  
DV170E0M-N30 Product SpecificationPAGE  
31 OF 34

## 12.0 APPENDIX


&lt; Figure 1. Uniformity Measurement Locations (9 points)&gt;




The White luminance uniformity on LCD surface is then expressed as :  $\Delta Y_9 = \text{Minimum Luminance of five points} / \text{Maximum Luminance of 9 points}$

## 12.0 APPENDIX

< Figure 2. Measurement Set Up >



< Figure 3. Response Time Testing >



**BOE**

PRODUCT GROUP

REV

ISSUE DATE


TFT- LCD PRODUCT

A

2023.03.21

SPEC. NUMBER  
S8-65-8D-229SPEC. TITLE  
DV170E0M-N30 Product SpecificationPAGE  
33 OF 34

&lt; Figure 4.TFT-LCD Module Outline Dimensions (Front View) &gt;



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	A	2023.03.21
SPEC. NUMBER	SPEC. TITLE	PAGE	
S8-65-8D-229	DV170E0M-N30 Product Specification	34	OF 34

## < Figure 5.TFT-LCD Module Outline Dimensions (Rear View) >

