



Kaohsiung Opto-Electronics Inc.

FOR MESSRS : \_\_\_\_\_

DATE : May 1<sup>st</sup>, 2012

## CUSTOMER'S ACCEPTANCE SPECIFICATIONS

### LMG7550XUFC


#### Contents

No.	ITEM	SHEET No.	PAGE
1	COVER	7B64PS 2701-LMG7550XUFC-5	1-1/1
2	RECORD OF REVISION	7B64PS 2702-LMG7550XUFC-5	2-1/2~2/2
3	MECHANICAL DATA	7B64PS 2703-LMG7550XUFC-5	3-1/1
4	ABSOLUTE MAXIMUM RATINGS	7B64PS 2704-LMG7550XUFC-5	4-1/1
5	ELECTRICAL CHARACTERISTICS	7B64PS 2705-LMG7550XUFC-5	5-1/2~2/2
6	OPTICAL CHARACTERISTICS	7B64PS 2706-LMG7550XUFC-5	6-1/2~2/2
7	BLOCK DIAGRAM	7B64PS 2707-LMG7550XUFC-5	7-1/1
8	INTERFACE TIMING CHART	7B64PS 2708-LMG7550XUFC-5	8-1/3~3/3
9	DIMENSIONAL OUTLINE	7B64PS 2709-LMG7550XUFC-5	9-1/3~3/3
10	APPEARANCE STANDARD	7B64PS 2710-LMG7550XUFC-5	10-1/5~5/5
11	PRECAUTION IN DESIGN	7B64PS 2711-LMG7550XUFC-5	11-1/4~4/4
12	DESIGNATION OF LOT MARK	7B64PS 2712-LMG7550XUFC-5	12-1/1
13	PRECAUTION FOR USE	7B64PS 2713-LMG7550XUFC-5	13-1/1

ACCEPTED BY: \_\_\_\_\_

PROPOSED BY: Kenthen

## 2. RECORD OF REVISION

DATE	SHEET No.	SUMMARY
MAR.27.'98	7B64PS 2710- LMG7550XUFC-2 PAGE 10-3/5	CHANGE: CONTRAST IRREGULARITY (SPOT) IS CHANGED.
Oct.18.'04	7B64PS 2712- LMG7550XUFC-3 PAGE 12-1/1	<p>12. DESIGNATION OF LOT MARK LOT MARK LOT MARK IS CONSISTED OF 4 DIGITS FOR PRODUCTION. LOT AND 8 DIGITS FOR PRODUCTION CONTROL.</p>  <p>12. DESIGNATION OF LOT MARK LOT MARK LOT MARK IS CONSISTED OF 4 DIGITS FOR PRODUCTION. LOT AND 6 DIGITS FOR PRODUCTION CONTROL.</p> <p>4 1 0 1 T</p> <p>T : MADE IN TAIWAN WEEK MONTH YEAR</p>
May.28.'07	7B64PS 2709- LMG7550XUFC-4 PAGE 9-3/3	9.3 Internal Pin Connection Changed : CFL I / F : Mitsumi M63M83 – 04 → JAE IL-G-4S-S3C2-SA

REV No.	ITEM	LOT No.
B	CFL I/F Connector : Mitsumi M63M83 - 04	-
C	CFL I/F Connector : JAE IL-G-4S-S3C2-SA	7102T

## 2. RECORD OF REVISION

DATE	SHEET No.	SUMMARY
May 01, '12	All pages	Company name changed: KAOHSIUNG HITACHI ELECTRONICS CO.,LTD. ↓ KAOHSIUNG OPTO-ELECTRONICS INC.

### 3. MECHANICAL DATA

(1) PART NAME LMG7550XUFC

(2) MODULE SIZE 264.0(W)mm\*183.0(H)mm\*9.0(D)mm max.

(3) DOT SIZE 0.3 (W)mm\*0.3 (H)mm

(4) DOT PITCH 0.33 (W)mm\*0.33 (H)mm

(5) NUMBER OF DOTS 640 (W) \* 480 (H)DOTS

(6) DUTY 1/244 (DISPLAY IS DIVIDED INTO 2 BLOCKS)

(7) LCD FILM TYPE BLACK/WHITE (NEGATIVE TYPE)  
THE UPPER POLARIZER IS ANTI-GLARE TYPE  
(HARDNESS:3H)  
THE BOTTOM POLARIZER IS TRANSMISSIVE  
TYPE.

(8) VIEWING DIRECTION 12 O'CLOCK

(9) BACK LIGHT COLD CATHODE FLUORESCENT LAMP

## 4. ABSOLUTE MAXIMUM RATINGS

### 4.1 ELECTRICAL ABSOLUTE MAXIMUM RATINGS.

VSS=0V:STANDARD

ITEM	SYMBOL	MIN.	MAX.	UNIT	REMARKS
POWER SUPPLY FOR LOGIC	VDD-VSS	0	6.5	V	
POWER SUPPLY FOR LC DRIVE	VDD-VEE	0	27.5	V	
INPUT VOLTAGE	Vi	-0.3	VDD+0.3	V	NOTE 1
INPUT CURRENT	II	0	1	A	
STATIC ELECTRICITY	-	-	-	-	NOTE 2

NOTE 1 :DISP.OFF,FRAME,LOAD,CP,UD0~UD3,LD0~LD3.

NOTE 2 :MAKE CERTAINS YOU ARE GROUNDED WHEN HANDLING LCM.

### 4.2 ENVIRONMENTAL ABSOLUTE MAXIMUM RATINGS.

ITEM	OPERATING		STORAGE		REMARKS
	MIN.	MAX.	MIN.	MAX.	
AMBIENT TEMPERATURE	0°C NOTE 6	45°C NOTE 7	-25°C	60°C	NOTE 2,3
HUMIDITY	NOTE 1		NOTE 1		WITHOUT CONDENSATION
VIBRATION	-	2.45m/s <sup>2</sup> (0.25G)	-	11.76m/s <sup>2</sup> (1.2G) NOTE 5	NOTE 4
SHOCK	-	29.4m/s <sup>2</sup> (3G)	-	490m/s <sup>2</sup> (50G) NOTE 5	3 TIMES FOR EACH DIRECTION OF +/-X/+/-Y/+/-Z PULSE WIDTH 10MS
CORROSIVE GAS	NOT ACCEPTABLE		NOT ACCEPTABLE		

NOTE 1 :Ta<=40°C:85%RH max.

Ta>40°C:ABSOLUTE HUMIDITY MUST BE LOWER

THAN THE HUMIDITY OF 85%RH AT 40°C.

NOTE 2 :Ta AT -25°C----- < 48H,AT 60°C----- < 168H.

NOTE 3 :BACKGROUND COLOR CHANGES SLIGHTLY DEPENDING ON AMBIENT  
TEMPERATURE. THIS PHENOMENON IS REVERSIBLE.

NOTE 4 :5Hz~500Hz (EXCEPT RESONANCE FREQUENCY) FOR EACH DIRECTION  
OF X/Y/Z.

ANY FAILURE CAUSED BY CONNECTOR LOOSENER WHILE TESTING  
SHALL BE IGNORED.

NOTE 5 :THIS MODULE SHOULD BE OPERATED NORMALLY AFTER FINISH  
THE TEST.

ANY FAILURE CAUSED BY CONNECTOR LOOSENER WHILE TESTING  
SHALL BE IGNORED.

NOTE 6 :HIGHER STARTING VOLTAGE OF CFL AND HIGHER LCD DRIVING  
VOLTAGE ARE NEEDED WHILE OPERATING AT 0°C. THE LIFE  
TIME CFL WILL BE REDUCED WHILE OPERATING AT 0°C. THE  
LIFE NEED TO MAKE SURE OF VALUE OF IL AND  
CHARACTERISTICS OF INVERTER. ALSO THE RESPONSE TIME AT 0°C  
WILL BE SLOWER.

NOTE 7 :THERE ARE POSSIBILITY THAT COLOR UN-UNIFORMITY HAPPENED  
WHILE OPERATING AT 45°C

## 5. ELECTRICAL CHARACTERISTICS OF LCM

### 5.1 ELECTRICAL CHARACTERISTICS

ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
POWER SUPPLY VOLTAGE FOR LOGIC	VDD-VSS	-	4.75	-	5.25	V
	VEE-VSS	-		-22V		
INPUT VOLTAE NOTE 1	VI	H LEVEL	0.7VDD	-	VDD	V
		L LEVEL	0	-	0.3VDD	V
POWER SUPPLY CURRENT FOR LOGIC NOTE 2	IDD	VDD-VSS=5.0V	-	25.0	30.0	mA
POWER SUPPLY CURRENT FOR LC DRIVING NOTE 2	IEE	VDD-VSS=5.0V	-	19.0	30.0	mA
RECOMMENDED LC DRIVING VOLTAGE NOTE 3	VDD-VEE	Ta=0°C , φ=0°	-	23.9	-	V
		Ta=25°C , φ=0°	-	22.7	-	V
		Ta=40°C , φ=0°	-	21.6	-	V
FRAME FREQUENCY NOTE4	fFRAME	-	69	-	110	Hz

NOTE 1 :DISP.OFF,FRAME,LOAD,CP,UD0~UD3, LD0~LD3.

NOTE 2 :fFRAME=140Hz,UD0~UD3=0,1,0,1,...,LD0~LD3=1,0,1,0,...

VDD-V0=22.7V,Ta=25°C

NOTE 3 :RECOMMENDED LC DRIVING VOLTAGE FLUCTUATE ABOUT ±1.0V  
BY EACH MODULE.

TEST PATTERN IS ALL "Q".

NOTE 4 :NEED TO MAKE SURE OF FLICKRING AND RIPPLING OF DISPLAY  
WHEN SETTING THE FRAME FREQUENCY IN YOUR SET.

## 5.2 ELECTRICAL CHARACTERISTICS OF BACKLIGHT

ITEM	SYMBOL	MIN.	TYP.	MAX.	UNIT	REMARKS
LAMP VOLTAGE	VL	-	430	-	Vrms	Ta=25°C
FREQUENCY	fL	50	-	70	KHz	Ta=25°C
LAMP CURRENT	IL	4	4.5	6	mArms	Ta=25°C
STARTING DISCHARGE VOLTAGE	VS NOTE 2	1000	-	-	Vrms	Ta=25°C

NOTE 1 :PLEASE CERTAINLY INFORM KOE BEFORE DESIGNING  
LAMP DRIVE CIRCUIT ACCORDING TO THE ABOVE SPECIFICATIONS.

NOTE 2 :STARING DISCHARGE VOLTAGE IS INCREASED WHEN LCM IS  
OPERATING AT LOWER TEMPERATURE. PLEASE CHECK THE  
CHARACTERISTICS OF INVERTER BERFORE APPLING TO YOUR SET.

NOTE 3 :AVERAGE LIFE TIME OF CFL WILL BE DECREASED WHEN LCM  
IS OPREATING AT LOWER TEMPERATURE.


## 6. OPTICAL CHARACTERISTICS

### 6.1 OPTICAL CHARACTERISTICS

Ta=25°C (BACKLIGHT ON)							
ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	REMARKS
VIEWING ANGLE	$\phi_2-\phi_1$	$K \geq 2.0$	30	40	-	deg	1,2
CONTRAST RATIO	K	$\phi=0^\circ \theta=0^\circ$	10	18	-	-	3
RESPONSE TIME (RISE)	tr	$\phi=0^\circ \theta=0^\circ$	-	160	-	ms	4
RESPONSE TIME (FALL)	tf	$\phi=0^\circ \theta=0^\circ$	-	110	-	ms	4


(MEASURE CONDITION BY KOE)

NOTE 1. DEFINITION OF  $\theta$  AND  $\phi$   
Z (NORMAL)




NOTE 3. DEFINITION OF CONTRAST "K"


$$K = \frac{\text{BRIGHTNESS ON SELECTED DOT (B1)}}{\text{BRIGHTNESS ON NON-SELECTED DOT (B2)}}$$




NOTE 2. DEFINITION OF VIEWING ANGLE  $\phi_1$  AND  $\phi_2$



CONTRAST RATIO K VS VIEWING ANGLE  $\phi$



NOTE 4. DEFINITION OF OPTICAL RESPONSE



## 6.2 OPTICAL CHARACTERISTICS BACKLIGHT

(LCM, BACKLIGHT ON, Ta=25°C)

ITEM	MIN.	TYP.	MAX.	UNIT	REMARKS
BRIGHTNESS	80.0	100.0	-	cd/m <sup>2</sup>	IL=5mA NOTE 1,2
RISE TIME	-	5	-	MINUTE	IL=5mA BRIGHTNESS 80%
BRIGHTNESS UNIFOMITY	-	-	+/-20	%	UNDERMENTIONED NOTE 1,3


CFL : INITAL , Ta=25°C , VDD-VEE=22.7V  
DISPLAY DATA SHOULD BE ALL "ON".

NOTE 1 MEASUREMENT AFTER 10 MINUTES OF CFL OPERATING.

NOTE 2 BRIGHTNESS CONTROL :100%


NOTE 3 MEASUREMENT OF THE FOLLOWING 9 PLACES ON THE DISPLAY.  
DEFINITION OF THE BRIGHTNESS TOLERANCE.

Y=60 Y=320 Y=580



$$\left( \frac{\text{MAX BRIGHTNESSW OR MIN BRIGHTNESS} - \text{AVERAGE BRIGHTNESS}}{\text{AVERAGE BRIGHTNESS}} \right) \times 100\%$$


## 7. BLOCK DIAGRAM



## 8. INTERFACE TIMING CHART

### 8.1 TIMING CHART

$37.6\mu\text{s} \leq T \leq 59.9\mu\text{s}$



NOTE (1) DUMMY DATA : "H" LEVEL.


NOTE (2) DO NOT INPUT OVER 244 PULSES TO LOAD.

## 8.2 TIMING CHARACTERISTICS


0°C<=Ta<=50°C

VDD=5V+/-0.25V


ITEM	SYMBOL	MIN.	TYP.	MAX.	UNIT
CLOCK FREQUENCY	f <sub>CP</sub>	-	-	6.5	MHz
CLOCK PULSE WIDTH	t <sub>W</sub>	63	-	-	ns
CLOCK PISE , FALL TIME	t <sub>r,tf</sub>	-	-	20	ns
DATA SET UP TIME	t <sub>DSU</sub>	50	-	-	ns
DATA HOLD TIME	t <sub>DHD</sub>	50	-	-	ns
LOAD SET UP TIME	t <sub>LSU</sub>	80	-	-	ns
LOAD→CLOCK TIME	t <sub>LC</sub>	120 80	-	-	ns
“FRAME” SET UP TIME	t <sub>SETUP</sub>	100	-	-	ns
“FRAME” HOLD TIME	t <sub>HOLD</sub>	100	-	-	ns
“LOAD” PULSE WIDTH	t <sub>WC</sub>	125	-	-	ns



### 8.3 TIMING OF POWER SUPPLY AND INTERFACE SIGNAL



### 8.4 POWER SUPPLY FOR LCM (EXAMPLE)



C1,C2 : 3.3μF(ALUMINIUM ELECTROLYTIC CAPACITOR)


VR : 10μ20KΩ

Tr : 2SA673APKC (HFE=100,IC=500mA)OR EQUIVALENT TR.

## 9. DIMENSIONAL OUTLINE

### 9.1 DIMENSIONAL OUTLINE

## 9.1 DIMENSIONAL OUTLINE



KAOHSIUNG OPTO-ELECTRONICS INC. SHEET No.


### Detail of D

### Detail of C

### Detail of B

PAGE 9-1/

## 9.2 DISPLAY PATTERN



### 9.3 INTERNAL PIN CONNECTION

INTERFACE	PIN NO.	SIGNAL	LEVEL	FUNCTION
LCM	I/F1	1	FRAME	H FIRST LINE MARKER
		2	LOAD	H→L DATA LATCH
		3	CP	H→L DATA SHIFT
		4	DISP.OFF	H/L H : ON / L : OFF
		5	VDD	- POWER SUPPLY FOR LOGIC
		6	VSS	- GND
		7	VEE	- POWER SUPPLY FOR LC
		8	UD0	H/L DISPLAY DATA (UPPER HALF)
		9	UD1	
		10	UD2	
		11	UD3	
		12	LD0	H/L DISPLAY DATA (LOWER HALF)
		13	LD1	
		14	LD2	
		15	LD3	

I/F1 : MOLEX / 53261-1510

(SUITABLE CONNECTOR : MOLEX / 51021-1500)

INTERFACE	PIN NO.	SIGNAL	LEVEL	FUNCTION
CFL	CFL I/F	1	H.V	- POWER SUPPLY FOR CFL
		2	N.C	-
		3	N.C	-
		4	GND	CFL GND


CFL I/F1 : JAE IL-G-4S-S3C2-SA

## 10. APPEARANCE STANDARD

### 10.1 APPEARANCE INSPECTION CONDITION

VISUAL INSPECTION SHOULD BE DONE  
UNDER THE FOLLOWING CONDITION.

- (1) IN THE DARK ROOM
- (2) WITH CFL PANEL LIGHTED WITH PRESCRIBED INVERTER CIRCUIT.
- (3) WITH EYES 25cm DISTANCE FROM LCM.
- (4) VIEWING ANGLE WITHIN 45 DEGREES FROM THE VERTICAL LINE TO THE CENTER OF LCD.



### 10.2 DEFINITION OF EACH ZONE

A ZONE : WITHIN THE EFFECTIVE DISPLAY AREA SPECIFIED AT PAGE 9-1/3 OF THIS DOCUMENT.

B ZONE : AREA BETWEEN THE WINDOW OF BEZEL LINE AND THE EFFECTIVE DISPLAY AREA LINE SPECIFIED AT PAGE 9-1/3 OF THIS DOCUMENT.



### 10.3 APPEARANCE SPECIFICATION

#### (1) LCD APPEARANCE

\*) IF THE PROBLEM OCCURES ABOUT THIS ITEM, THE RESPONSIBLE PERSON OF BOTH PARTY (CUSTOMER AND KOE) WILL DISCUSS MORE DETAIL.

No.	ITEM	CRITERIA		A	B		
L C D	SCRATCHES	SERIOUS ONE IS NOT ALLOWED		*	-		
	DENT	SERIOUS ONE IS NOT ALLOWED		*	-		
	WRINKLES IN POLARIZER	SERIOUS ONE IS NOT ALLOWED		*	-		
	BUBBLES	AVERAGE DIAMETER D(mm)	MAXIMUM NUMBER ACCEPTABLE	O	-		
		$D \leq 0.3$	IGNORED				
		$0.3 < D \leq 0.5$	3				
		$0.5 < D \leq 1.0$	1				
		$1.0 < D$	NONE				
	STAINS, FOREIGN MATERIALS DARK SPOT	FILAMENTOUS		O	*		
		LENGTH L(mm)	WIDTH W(mm)				
		$L \leq 2.0$	$W \leq 0.03$				
		$L \leq 2.0$	$0.03 < W \leq 0.1$				
		$2.0 \leq L \leq 5.0$	$0.03 < W \leq 0.1$				
		ROUND					
		AVERAGE DIAMETER D(mm)	MAXIMUM NUMBER ACCEPTABLE				
		$D < 0.25$	IGNORED				
		$0.25 \leq D < 0.35$	4				
		$0.35 \leq D$	NONE				
	THOSE WIPE OUT EASILY ARE ACCEPTABLE			O	O		
PINHOLE	$(A+B)/2 \leq 0.15$ MAXIMUM NUMBER : IGNORED			O	-		
	$0.15 < (A+B)/2 \leq 0.3$ MAXIMUM NUMBER : 10						
	$C \leq 0.03$ MAXIMUM NUMBER : IGNORED						


No.	ITEM	CRITERIA			A	B
		AVERAGE DIAMETER	MAXIMUM NUMBER	MINIMUM SPACE		
L	CONTRAST IRREGULARITY (SPOT)	D(mm)	ACCEPTABLE			
		$D \leq 0.3$	IGNORED	-		
		$0.3 < D \leq 0.45$	15	20mm	O	-
		$0.45 < D \leq 0.6$	5	20mm		
		$0.6 < D \leq 0.8$	3	50mm		
		$0.8 < D$	NONE	-		
C	CONTRAST IRREGULARITY (LINE) ( A PAIR OF SCRATCH)	WIDTH	LENGTH	MAXIMUM NUMBER	MINIMUM	
		W(mm)	L(mm)	ACCEPTABLE	SPACE	
		$W \leq 0.1$	$L \leq 3.0$	IGNORED	20mm	
		$0.1 < W \leq 0.15$	$L \leq 2.0$	3	20mm	O
		$0.15 < W \leq 0.25$	$L \leq 1.5$	3	20mm	-
		$0.25 < W \leq 0.35$	$L \leq 1.0$	3	20mm	
D		$0.35 < W$	-	NONE	-	

## (2) CFL BACKLIGHT APPEARANCE

No.	ITEM	CRITERIA			A	B	
C F L	DARK SPOTS	AVERAGE DIAMETER		MAXIMUM NUMBER		O -	
	WHITE SPOT	D(mm)		ACCEPTABLE			
	FOREIGN MATERIALS (SPOT)	D $\leq$ 0.4		IGNORED			
		0.4 $<$ D		NONE			
B A C K	FOREIGN MATERIALS (LINE)	WIDTH	LENGTH	MAXIMUM NUMBER	O -	O -	
		W(mm)	L(mm)	ACCEPTABLE			
		W $<$ 0.2	L $\leq$ 2.5	1			
			2.5 $<$ L	NONE			
L I G H T	SCRATCHES	0.2 $<$ W	-	NONE	O -	O -	
		WIDTH	LENGTH	MAXIMUM NUMBER			
		W(mm)	L(mm)	ACCEPTABLE			
		W $\leq$ 0.1	-	IGNORED			
H		0.1 $\leq$ 0.2	L $\leq$ 11.0	1	O -	O -	
			11.0 $<$ L	NONE			
		0.2 $<$ W	-	NONE			

NOTE

(1) DEFINITION OF AVERAGE DIAMETER D




$$D = \frac{a+b}{2}$$

(2) DEFINITION OF LENGTH L AND WIDTH W



(3) DEFINITION OF PINHOLE




C : SALIEN

## 11. PRECAUTION IN DESIGN

### 11.1 MOUNTING METHOD

SINCE THE MODULE IS SO CONSTRUCTED AS TO BE FIXED BY UTILIZING FITTING HOLES IN THE MODULE AS SHOWN BELOW, IT IS NECESSARY TO TAKE CONSIDERATION THE FOLLOWING ITEMS ON ATTACHMENT TO A FRAME.



- (1) USE OF PROTECTIVE PLATE, MADE OF AN ACRYLIC PLATE, ETC, IN ORDER TO PROTECT A POLARIZER AND LC CELL.
- (2) TO PREVENT THE MODULE COVER FROM BEING PRESSED, THE SPACERS BETWEEN THE MODULE AND THE FITTING PLATES SHOULD BE LONGER THAN 0.5mm.
- (3) WE RECOMMEND YOU TO USE PROTECTIVE SPACER AS FIGURE FOR PROTECTING THE MODULE FROM ANY KIND OF SHOCK TO YOUR SET.

### 11.2 LC DRIVING VOLTAGE (VEE) AND VIEWING ANGLE RANGE.

SETTING VEE OUT OF THE RECOMMENDED CONDITION WILL BE A CAUSE FOR A CHANGE OF VIEWING ANGLE RANGE.

### 11.3 CAUTION AGAINST STATIC CHARGE

AS THIS MODULE IS PROVIDED WITH C-MOS LSI, THE CARE TO TAKE SUCH A PRECAUTION AS TO GROUNDING THE OPERATOR'S BODY IS REQUIRED WHEN HANDLING IT.

### 11.4 POWER ON SEQUENCE

INPUT SIGNALS SHOULD NOT BE APPLIED TO LCD MODULE BEFORE POWER SUPPLY VOLTAGE IS APPLIED AND REACHES TO SPECIFIED VOLTAGE (5+/-0.25V).

IF ABOVE SEQUENCE IS NOT KEPT, C-MOS LSIS OF LCD MODULES MAY BE DAMAGED DUE TO LATCH UP PROBLEM.

### 11.5 PACKAGING

- (1) NO. LEAVING PRODUCTS IS PREFERABLE IN THE PLACE OF HIGH HUMIDITY FOR A LONG PERIOD OF TIME. FOR THEIR STORAGE IN THE PLACE WHERE TEMPERATURE IS 35°C OR HIGHER, SPECIAL CARE TO PREVENT THEM FROM HIGH HUMIDITY IS REQUIRED. A COMBINATION OF HIGH TEMPERATURE AND HIGH HUMIDITY MAY CAUSE THEM POLARIZATION DEGRADATION AS WELL AS BUBBLE GENERATION AND POLARIZER PEEL-OFF. PLEASE KEEP THE TEMPERATURE AND HUMIDITY WITHIN THE SPECIFIED RANGE FOR USE AND STORING.
- (2) SINCE UPPER POLARIZERS AND LOWER ALUMINUM PLATES TEND TO BE EASILY DAMAGED, THEY SHOULD BE HANDLED WITH FULL CARE SO AS NOT TO GET THEM TOUCHED, PUSHED OR RUBBED BY A PIECE OF GLASS.  
TWEEZERS AND ANYTHING ELSE WHICH ARE HARDER THAN A PENCIL LEAD 3H.
- (3) AS THE ADHESIVES USED FOR ADHERING UPPER/LOWER POLARIZERS AND ALUMINUM PLATES ARE MADE OF ORGANIC SUBSTANCES WHICH WILL BE DETERIORATED BY A CHEMICAL REACTION WITH SUCH CHEMICALS AS ACETONE, TULUENE ETHANOLE AND ISOPROPYLALCOHOL. THE FOLLOWING SOLVENTS ARE RECOMMENDED FOR USE:  
NORMAL HEXANE  
PLEASE CONTACT US WHEN IT IS NECESSARY FOR YOU TO USE CHEMICALS OTHER THAN THE ABOVE.
- (4) LIGHTLY WIPE TO CLEAN THE DIRTY SURFACE WITH ABSORBENT COTTON WASTE OR OTHER SOFT MATERIAL LIKE CHAMOIS, SOAKED IN THE CHEMICALS RECOMMENDED WITHOUT SCRUBBING IT HARDLY. TO PREVENT THE DISPLAY SURFACE FROM DAMAGE AND KEEP THE APPEARANCE IN GOOD STATE, IT IS SUFFICIENT, IN GENERAL, TO WIPE IT WITH ABSORBENT COTTON.

- (5) IMMEDIATELY WIPE OFF ASLIVA OR WATER DROP ATTACHED ON THE DISPLAY AREA BECAUSE ITS LONG PERIOD ADHERANCE MAY CAUSE DEFORMATION OR FADED COLOR ON THE SPOT.
- (6) FOGY DEW DEPOSITED ON THE SURFACE AND CONTACT TERMINALS DUE TO COLDNESS WILL BE A CAUSE FOR POLARIZER DAMAGE, STAIN AND DIRT ON PRODUCT. WHEN NECESSARY TO TAKE OUT THE PRODUCTS FROM SOME PLACE AT LOW TEMPERATURE FOR TEST, ETC. IT IS REQUIRED FOR THEM TO BE WARMED UP IN A CONTAINER ONCE AT THE TEMPERATURE HIGHER THAN THAT OF ROOM.
- (7) TOUCHING THE DISPLAY AREA AND CONTACT TERMINALS WITH BARE HANDS AND CONTAMINATING THEM ARE PROHIBITED, BECAUSE THE STAIN ON THE DISPLAY AREA AND POOR INSULATION BETWEEN TERMINALS ARE OFTEN CAUSED BY BEING TOUCHED BY BARE HANDS.  
(THERE ARE SOME COSMETICS DETRIMENTAL TO POLARIZERS.)
- (8) IN GENERAL THE QUALITY OF GLASS IS FRAGILE SO THAT IT TENDS TO BE CRACKED OR CHIPPED IN HANDLING, SPECIALLY ON ITS PERIPHERY. PLEASE BE CAREFUL NOT TO GIVE IT SHARP SHOCK CAUSED BY DROPPING DOWN, ECT.

#### 11.6 CAUTION FOR OPERATION

- (1) IT IS AN INDISPENSABLE CONDITION TO DRIVE LCD'S WITHIN THE SPECIFIED VOLTAGE LIMIT SINCE THE HIGHER VOLTAGE THAN THE LIMIT CAUSES THE SHORTER LCD LIFE. AN ELECTROCHEMICAL REACTION DUE TO DIRECT CURRENT CAUSES LCD'S UNDESIRABLE DETERIORATION, SO THAT THE USE OF DIRECT CURRENT DRIVER SHOULD BE AVOIDED.
- (2) RESPONSE TIME WILL BE EXTREMELY DELAYED AT LOWER TEMPERATURE THAN THE OPERATING TEMPERATURE RANGE AND ON THE OTHER HAND AT HIGHER TEMPERATURE LCD'S SHOW DARK BULE COLOR IN THEM. .HOWEVER THOSE PHENOMENA DO NOT MEAN INPEDIMENT OR OUT OF ORDER WITH LCD'S WHICH WILL COME BACK IN THE SPECIFIED OPERATING TEMPERATURE RANGE.
- (3) IF THE DISPLAY AREA IS PUSHED HARD DURING OPERATION, SOME FONT WILL BE ABNORMALLY DISPLAYED BUT IT RESUMES NORMAL CONDITION AFTER TURNING OFF ONCE.
- (4) A SLIGHT DEW DEPOSITING ON TERMINALS IS A CAUSE FOR ELECTROCHEMICAL REACTION RESULTING IN TERMINAL OPEN CIRCUIT. USAGE UNDER THE RELATIVE CONDITION OF 40°C 50%RH LESS IS REQUIRED.

## 11.7 STORAGE

IN CASE OF STORING FOR A LONG PERIOD OF TIME (FOR INSTANCE, FOR YEARS) FOR THE PURPOSE OF REPLACEMENT USE, THE FOLLOWING WAYS ARE RECOMMENDED.

- (1) STORAGE IN A POLYETHYLENE BAG WITH THE OPENING SEALED SO AS NOT TO ENTER FRESH AIR OUTSIDE IN IT, AND WITH NO DESICCANT.
- (2) PLACING IN A DARK PLACE WHERE NEITHER EXPOSURE TO DIRECT SUNLIGHT NOR LIGHT IS, KEEPING TEMPERATURE IN THE RANGE FROM 0°C TO 35°C.
- (3) STORING WITH NO TOUCH ON POLARIZER SURFACE BY ANYTHING ELSE.  
(IT IS RECOMMENDED TO STORE THEM AS THEY HAVE BEEN CONTAINED IN THE INNER CONTAINER AT THE TIME OF DELIVERY FROM US.)

## 11.8 SAFETY


- (1) IT IS RECOMMENDABLE TO CRUSH DAMAGED OR UNNECESSARY LCD'S INTO PIECES AND WASH OFF LIQUID CRYSTAL BY EITHER OF SOLVENTS SUCH AS ACETONE AND ETHANOL, WHICH SHOULD BE BURNED UP LATER.
- (2) WHEN ANY LIQUID LEAKED OUT OF A DAMAGED GLASS GALL COMES IN CONTACT WITH YOUR HANDS, PLEASE WASH IT OFF WELL WITH SOAP AND WATER.

## 12. DESIGNATION OF LOT MARK

### 12.1 LOT MARK

LOT MARK IS CONSISTED OF 4 DIGITS FOR PRODUCTION.

LOT AND 6 DIGITS FOR PRODUCTION CONTROL.



YEAR	FIGURE IN LOT MARK
2012	2
2013	3
2014	4
2015	5
2016	6

MONTH	FIGURE IN LOT MARK	MONTH	FIGURE IN LOT MARK
JAN.	01	JULY.	07
FEB.	02	AUG.	08
MAR.	03	SEPT.	09
APR.	04	OCT.	10
MAY.	05	NOV.	11
JUNE.	06	DEC.	12

WEEK (DAY IN CALENDAR)	FIGURE IN LOT MARK
1~7	1
8~14	2
15~21	3
22~28	4
29~31	5

### 12.2 REVISION

REV No.	ITEM	LOT No.
B	CFL I/F Connector : Mitsumi M63M83 - 04	-
C	CFL I/F Connector : JAE IL-G-4S-S3C2-SA	7102T

### 12.3 LOCATION OF LOT MARK

on the back side of LCM

4 1 0 1 \* \* \* \* \* \*

## 13. PRECAUTIPON FOR USE

- (1) A LIMIT SAMPLE SHOULD BE PROVIDED BY THE BOTH PARTIES ON AN OCCASION WHEN THE BOTH PARTIES AGREED ITS NECESSITY. JUDGEMENT BY A LIMIT SAMPLE SHALL TAKE EFFECT AFTER THE LIMIT SAMPLE HAS BEEN EATABLISHED AND CONFIRMED BY THE BOTH PARTIES.
- (2) ON THE FOLLOWING OCCASIONS , THE HANDLING OF THE PROBLEM SHOULD BE DECIDED THROUGH DISCUSSION AND AGREEMENT BETWEEN RESPONSIBLE PERSONS OF THE BOTH PARTIES.
  - (1) WHEN A QUESTION IS ARISEN IN THE SPECIFICATIONS.
  - (2) WHEN A NEW PROBLEM IN ARISEN WHICH IS NOT SPECIFIED IN THIS SPECIFICATIONS.
  - (3) WHEN AN INSPECTION SPECIFICATIONS CHANGE OR OPERATING CONDITION CHANGE IN CUSTOMER IS REPORTED TO KOE, AND SOME PROBLEM IS ARISEN IN THIS SPECIFICATION DUE TO THE CHANGE.
  - (4) WHEN A NEW PROBLEM IS ARISEN AT THE CUSTOMER'S OPERATING SET FOR SAMPLE EVALUATION IN THE CUSTOMER SITE.
- (3) REGARDING THE TREATMENT FOR MAINTENANCE AND REPAIRING, BOTH PARTIES WILL DISSCUSS IT IN SIX MONTHS LATER AFTER LATEST DELIVERY OF THIS PRODUCT.

THE PRECAUTION THAT SHOULD BE OBSERVED WHEN HANDLING LCM HAVE BEEN EXPLAIND ABOVE. IF ANY POINTS ARE UNCLEAR OF IF YOU HAVE ANY REQUESTS, PLEASE CONTACT KOE.